Algorithms Lab 2

The in-lab problems are to be solved during the lab time. Work with your team, but write your solutions individually. You do not need to turn in your answers, only discuss them with me. Ask me for feedback on how you write your answers as well.

The homework problem set is due on Wed 9/24. Work with your team, but write your solutions individually. List the people with whom you discussed the problems.

1 In lab exercises

- 1. Find a simple formula for $\sum_{k=1}^{n} (2k-1)$.
- 2. (CLRS 3-4.a) Prove or disprove: f = O(g) implies that g = O(f).
- 3. Prove or disprove: f = O(g) implies that $g = \Omega(f)$.

2 Homework problems

1. Consider the following code for BubbleSort that we discussed in class:

BUBBLE-SORT(A) 1 For k = 1 to n - 12 // do a bubble pass 3 For i = 0 to n - 24 if A[i] > A[i + 1]: swap

(b) Show how to change the code so that the algorithm dos not do any redundant bubblepasses (i.e. if the input needs only 3 bubble passes to be sorted, the algorithm does only 3 passes).

⁽a) Give the best-case and worst-case running time of the algorithm. Express them as $\Theta()$ bounds and give a brief justification.

Find a tight bound for the solution of the following recurrences using iteration.

- 2. T(n) = T(n/3) + 13. T(n) = T(n/3) + n
- 4. $T(n) = T(\sqrt{n}) + 1$
- 5. T(n) = T(n-1) + n
- 6. $T(n) = 7T(n/2) + n^3$
- 7. $T(n) = 7T(n/2) + n^2$