


Client-Server Architecture



File I/O

```
int open(char* path, int flags, ...)
```

```
int read(int fd, void* buf, int nbytes)
```

```
int write(int fd, void* buf, int nbytes)
```

```
int close(int fd)
```

Socket I/O: socket

```
int socket(int domain, int type,  
           int protocol)
```

- domain = AF_INET
- type = SOCK_STREAM
- protocol = 0 (or IPPROTO_TCP)

Socket I/O: bind

```
int bind(int sock, struct sockaddr* addr,  
         int addrlen)
```

- sock = socket file descriptor
- addr: see below
- addrlen = sizeof(addr)

```
struct sockaddr_in {  
    short sin_family; // --> AF_INET  
    u_short sin_port; // --> htons(portnum)  
    struct in_addr sin_addr;  
    // --> .s_addr = htonl(INADDR_ANY)  
}
```

Socket I/O: listen

```
int listen(int sock, int backlog)
```

- sock = socket file descriptor
- backlog = max # of unaccepted connections (e.g. 10)

Socket I/O: accept

```
int accept(int sock, struct sockaddr* addr,  
           int* addrlenp)
```

- sock = listening socket
- addr gets filled in with client info
- addrlen = pointer to sizeof(struct sockaddr_in)


Blocking call!

Socket I/O: send/recv


```
int send(int sock, char* msg, int msglen,  
        int flags)
```

```
int recv(int sock, char* msg, int msglen,  
        int flags)
```

Client-Server Architecture



Processes and Threads



Creating Processes and Threads

- Processes:

- `int fork()`

- Threads:

```
int pthread_create(pthread_t* thr,  
                  const pthread_attr_t* attr,  
                  void* (*start_routine)(void*),  
                  void* arg)
```

`attr`: usually `NULL`

`start_routine`: function to execute

`arg`: argument to function